

**METHOD AND APPARATUS FOR MEMBRANE
RECIRCULATION AND CONCENTRATE ENERGY RECOVERY
IN A REVERSE OSMOSIS SYSTEM**

Related Applications

The present application relates to U.S. Patent Application 09/491,769 entitled "Hydraulic Energy Recovery Device" filed January 26, 2000, and U.S. Patent Application (Attorney Docket No OKL-
5 0118PA) entitled "Method And Apparatus for Boosting Interstage Pressure In A Reverse Osmosis System", each of which are hereby incorporated by reference.

Technical Field

The present invention relates generally to a reverse osmosis systems suitable for desalinization
10 of water, and more specifically, to a recirculation system and concentrate energy recovery in a reverse osmosis system.

Background of the Invention

Reverse osmosis (RO) is a process widely used for desalinization of water. Reverse osmosis
15 membranes are contained in a process chamber into which pressurized feedwater is admitted. A portion of the pressurized water permeates across the membrane and exits the process chamber as purified water at a low pressure and is referred to as
20 permeate. The remainder of the water, still at high pressure, exits the process chamber and is referred to as a concentrate.

001001 69420460

about 30 psi in the present example. Thus, feed pump 12 must pressurize the recirculation flow as well as the feed flow.

Another known arrangement similar to Figure 1 is illustrated having the same components illustrated with the same reference numerals. In this embodiment, a pump 30 driven by a motor 32 couples concentrate at an elevated pressure above that of the feed stream.

One problem with these types of systems is that although they are more energy efficient than other known systems, energy dissipated in control valve 28 cannot be recovered. Another drawback to this type of system is that recirculation pump 30 is expensive because of the high working pressure. Another drawback to the system is that the motor 32 consumes a substantial amount of energy.

Summary of the Invention

It is therefore one object of the invention to provide a reverse osmosis system that uses concentrate recirculation to allow the membrane to operate efficiently while recovering otherwise wasted energy.

In one aspect of the invention a process chamber preferably a reverse osmosis chamber, has a feed inlet, a low pressure outlet, and a high pressure outlet. A feed pump is used to increase the pressure of feed fluid to feed inlet.

00702469-103100

A common shaft is used to rotatably couple a booster and an energy recovery turbine together. The energy recovery turbine is fluidically coupled to the high pressure outlet to drive the booster pump.

5 The booster pump is positioned between the feed pump and process chamber and increases the pressure of feed fluid.

In a further aspect of the invention, a method for operating a reverse osmosis system

10 comprises the steps of:

boosting a pressure of fluid output from a feed pump prior to entering to a first process chamber using from a first portion of a high pressure fluid from a high pressure outlet of a first process

15 chamber;

recirculating a second portion of the high pressure fluid; and

fluidically coupling the second portion of the high pressure fluid between the feed pump and the

20 process chamber.

One advantage of the present invention is that energy-wasting throttle valves and bypass lines have been eliminated from the reverse osmosis process. Another advantage of the invention is that

25 more energy is recovered from the process lowering the overall cost of operating such a process. Another advantage is that the components can be combined into a single package.

Other objects and features of the present

30 invention will become apparent when viewed in light

of the detailed description of the preferred embodiment when taken in conjunction with the attached drawings and appended claims.

Brief Description of the Drawings

Figure 1 is a schematic view of a first
5 known reverse osmosis system of the prior art.

Figure 2 is a schematic view of a second known reverse osmosis system of the prior art.

Figure 3 is a schematic view of a first
10 embodiment of a reverse osmosis system according to the present invention.

Figure 4 is a schematic view of a second embodiment of a reverse osmosis system according to the present invention.

Figure 5 is a schematic view of a third
15 embodiment of a reverse osmosis system according to the present invention.

Figure 6 is a cross sectional view of a jet pump of Figures 4 and 5.

08-06-2013 10:30

The present invention is described with respect to various preferred embodiments and preferred system uses. One skilled in the art would recognize various alternatives without varying from the spirit of the invention such as non-desalinization reverse osmosis systems.

An improved reverse osmosis system 110 is illustrated having a feed pump 112 which is driven by a motor 114 to pressurize feed fluid from a feed input 116. Pressurized feed fluid leaves pump 112 through an output 118, travels through a valve 119 and enters a first reverse osmosis process chamber 120. The first reverse osmosis process chamber 120 has a membrane 121 therein for filtering feed fluid. The process chamber 120 has a permeate header 122 through which low pressure permeate that has passed through the membrane 121 is removed from the reverse osmosis chamber 120. Reverse osmosis chamber 120 also has a concentrate output 124 which removes concentrate from the reverse osmosis chamber 120 at a high pressure. The concentrate output 124 in this case has two paths; a first channel 136 and a second

channel 138. A portion of the concentrate flows into each channel 136, 138.

First channel 136 directs a portion of concentrate in series through an energy recovery turbine 133 that is coupled to a common shaft 134 and a booster pump 135. Booster pump 135 is therefore driven by concentrate flow through channel 136 which drives turbine 133. The output of turbine 133 is concentrate with a substantial portion of the energy (preferably substantially all) contained therein removed.

Second channel 138 has a control valve 140 coupled in series therein to control the flow of concentrate through channel 136 and 138. Second channel 138 after control valve 140 directs concentrate between feed pump 112 and process chamber 120. In this embodiment, concentrate is preferably directed between feed pump 112 and booster pump 135.

Another known arrangement similar to Figure 1 is illustrated in Figure 4 also with reference to Figure 6 having the same components of Figure 3 illustrated with the same reference numerals. In this embodiment, first channel 136 is configured in a similar manner to that of Figure 3. Channel 138, however, is configured differently than that of Figure 3 by inserting a jet pump 142 therein. Jet pump 142 is positioned between feed pump 112 and process chamber 120. In this embodiment, jet pump 142 is preferably positioned between feed pump 112 and booster pump 135, and more specifically between

control valve 119 and booster pump 135. Jet pump 142 has a driving fluid input 144 coupled to concentrate output 124. Thus, the driving fluid of jet pump 142 is the recirculating flow whereas the pumped fluid is the feed flow from feed pump 112. By eliminating the control valve 140 from Figure 3, a portion of the energy that would have been lost is used to pressurize the combined feed and recirculation flow. Jet pump 142 has a pumped fluid input 146 used to receive feed fluid from feed pump 112. Jet pump 142 has a jet pump output 148 that directs fluid to booster pump 135.

Referring now to Figure 5, a similar arrangement to that of Figure 4 is illustrated using the same reference numerals for the same components of Figure 4. In this embodiment, jet pump 142 is positioned between booster pump 135 and process chamber 120. In this embodiment, however, the position of jet pump 142 is such that driving fluid input 144 is coupled to the output of booster pump 135 and the pressure of recirculating concentrate at pumped fluid input 146 is increased. In this embodiment, the most efficient arrangement depends on the ratio of feed flow to the recirculating flow. Generally, jet pump 142 is more efficient when the driving flow exceeds the pumped flow.

In operation, each of the embodiments of the present invention harnesses the energy from the concentrate output of the process chamber through two output channels. The first channel 136 is used to power an energy recovery turbine 133 to increase the

pressure of the feed fluid into process chamber 120. The second channel 138 is used to provide recirculation to process chamber 120 between feed pump 112 and process chamber 120. In the first
 5 embodiment, the second channel is coupled directly to the feed flow after feed pump 112 but before booster pump 135. Thus, the concentrate is recirculated through booster pump 135 and into process chamber 120 to obtain a predetermined velocity. In the second
 10 and third embodiments, a jet pump is used to further increase and harness the energy from the second channel 138. In the second embodiment, the pump fluid is the fluid from feed pump 112. In the third embodiment, the pump fluid is the concentrate.

15 While particular embodiments of the invention have been shown and described, numerous variations and alternate embodiments will occur to those skilled in the art. Accordingly, it is intended that the invention be limited only in terms
 20 of the appended claims.